

属性	
应用范围	农业技术 工业与建筑行业
特殊的属性	由于配有高抗断强度的衬里而特别结实耐用
内胶层	PVC
增强层	织物衬里
外胶层	NBR 带纵向保护条
颜色	黑色
温度 min.	-20 °C
温度 max.	100 °C
适用介质	水 空气 油 汽油



也适用于空气、油、汽油

货品					
名称	英寸	内径-Ø ^(mm)	壁厚 (mm)	工作压力 (bar)	卷长 (m)
AGRI WAS 19 LR	3/4"	19	1,5	25,0	100
AGRI WAS 25 LR	1"	25	1,5	25,0	100
AGRI WAS 32 LR	1.1/4"	32	1,5	20,0	100
AGRI WAS 38 LR	1.1/2"	38	1,5	16,0	100
AGRI WAS 52 LR	2"	52	2,0	16,0	100
AGRI WAS 65 LR	2.1/2"	65	2,0	16,0	100
AGRI WAS 76 LR	3"	75	2,5	16,0	100
AGRI WAS 90 LR	3.1/2"	90	2,5	16,0	100
AGRI WAS 102 LR	4"	102	2,5	16,0	100
AGRI WAS 127 LR	5"	127	3,0	16,0	100
AGRI WAS 152 LR	6"	152	3,0	16,0	100

BD = 工作压力