

属性

应用范围	农业技术 建筑行业 采矿设备 造船业
特殊的属性	最高的抗拉和抗断裂强度 压力下无膨胀 可扁平卷起并无中间连接
内胶层	PVC
增强层	一层聚酯编织增强层
外胶层	PVC
颜色	蓝色
温度 min.	-10 °C
温度 max.	60 °C
适用介质	水



货品

名称	英寸	内径-Ø (mm)	BD* 20°C下 (bar)	爆破压力 (bar)	卷长 (m)
EURO WAS 1 BL	1"	25	8,5	25,5	100
EURO WAS 1 1/4 BL	1.1/4"	32	8,5	25,5	100
EURO WAS 1 1/2 BL	1.1/2"	38	8,5	25,5	100
EURO WAS 2 BL	2"	51	6,5	19,5	100
EURO WAS 2 1/2 BL	2.1/2"	63	6,5	19,5	100
EURO WAS 3 BL	3"	76	5,5	16,5	100
EURO WAS 4 BL	4"	102	5,5	16,5	100
EURO WAS 5 BL	5"	127	3,0	9,0	100
EURO WAS 6 BL	6"	152	3,0	9,0	100
EURO WAS 8 BL	8"	204	2,5	7,0	100

BD = 工作压力