WAS STRAHL 建筑用水软管



属性	
特殊的属性	极其柔韧和牢固 不含LABS、分离剂和油脂 流动阻力小
内胶层	黑色无气孔光滑EPDM内层
增强层	人造纤维纱线
外胶层	EPDM 对臭氧和紫外线辐射不敏感
颜色	黑色
温度 min.	-40 °C
温度 max.	95 °C
温度范围	温度峰值至110°C
适用介质	水



提示

工作压力指的是在室温下

贞 丽							
英寸	内径-Ø _(mm)	壁厚 (mm)	工作压力 (bar)	最小弯曲半径 (mm)	卷长 (m)		
3/8"	10	3,5	20,0	60	50		
1/2"	13	3,0	20,0	80	40		
5/8"	16	3,5	20,0	100	40		
3/4"	19	4,0	20,0	120	40		
1"	25	4,5	20,0	150	40		
1.1/4"	32	6,0	20,0	200	50		
	3/8" 1/2" 5/8" 3/4" 1"	3/8" 10 1/2" 13 5/8" 16 3/4" 19 1" 25	(mm) (mm) 3/8" 10 3,5 1/2" 13 3,0 5/8" 16 3,5 3/4" 19 4,0 1" 25 4,5	(mm) (mm) (bar) 3/8" 10 3,5 20,0 1/2" 13 3,0 20,0 5/8" 16 3,5 20,0 3/4" 19 4,0 20,0 1" 25 4,5 20,0	(mm) (mm) (bar) (mm) 3/8" 10 3,5 20,0 60 1/2" 13 3,0 20,0 80 5/8" 16 3,5 20,0 100 3/4" 19 4,0 20,0 120 1" 25 4,5 20,0 150		