PYRO WAS RT 消防折叠软管



| 属性 | |
|-------|---|
| 应用范围 | 消防 |
| 特殊的属性 | 采用耐老化耐臭氧的EPDM化合物 高弹性和延展性, 高粘着力 采用特殊的硫化工艺加工 高耐磨 |
| 标准 | DIN 14.811 BS 6391 |
| 内胶层 | 高强度复合聚酯纤维, 双层捻线圆形编织工艺 |
| 颜色 | 红色 |
| 适用介质 | 水 |



| 货品 | | | | | | | | |
|----------------|--------|-------------------------|---------------|---------------|---------------|--------------|--|--|
| 名称 | 英寸 | 内径-Ø _(mm) | 工作压力 (bar) | 试验压力 (bar) | 破裂压力 (bar) | 卷长 (m) | | |
| PYRO WAS 38 RT | 1.1/2" | 38 | 16,0 | 25 | 50 | 15 / 20 / 30 | | |
| PYRO WAS 52 RT | 2" | 52 | 16,0 | 25 | 50 | 15 / 20 / 30 | | |
| PYRO WAS 63 RT | 2.1/2" | 63 | 16,0 | 25 | 50 | 15 / 20 / 30 | | |
| PYRO WAS 75 RT | 3" | 75 | 16,0 | 25 | 50 | 15 / 20 / 30 | | |