

属性	
应用范围	系统工程 工业与建筑行业
接口 1	BSP内螺纹,圆柱形
接口 2	软管接口
适用介质	压缩空气
原料	钢
表面保护	电镀涂层



提示

用软管夹DIN 20039 B接入

描述

扭转的套管外形使软管位置可靠固定 实现最大流量的最大钻孔

货品

立 戸 細 冷								
	用于软管-ID (mm)	Ø ID (mm)	长度 (mm)	螺纹长度 (mm)	套管长度 (mm)	Ø 保险环 _(mm)	SW (mm)	工作压力 巴
G 3/4" -14	19	15,00	71	19	40	32	32	PN 25
G 1" -11	19	15,00	73	20	40	32	41	PN 25
G 1" -11	25	20,00	75	20	41	36	41	PN 25
G 1.1/4" -11	25	20,00	80	23	41	36	50	PN 25
G 1.1/4" -11	32	25,00	86	23	48	45	50	PN 25
	6 3/4" -14 6 1" -11 6 1" -11 6 1.1/4" -11	(mm) 6 3/4" -14 19 6 1" -11 19 6 1" -11 25 6 1.1/4" -11 25	(mm) (mm) 6 3/4" -14 19 15,00 6 1" -11 19 15,00 6 1" -11 25 20,00 6 1.1/4" -11 25 20,00	(mm) (mm) (mm) 6 3/4" -14 19 15,00 71 6 1" -11 19 15,00 73 6 1" -11 25 20,00 75 6 1.1/4" -11 25 20,00 80	(mm) (mm) (mm) (mm) 6 3/4" -14 19 15,00 71 19 6 1" -11 19 15,00 73 20 6 1" -11 25 20,00 75 20 6 1.1/4" -11 25 20,00 80 23	(mm) <th< td=""><td>(mm) (mm) <th< td=""><td>(mm) (mm) <th< td=""></th<></td></th<></td></th<>	(mm) <th< td=""><td>(mm) (mm) <th< td=""></th<></td></th<>	(mm) <th< td=""></th<>

SW = 对应边宽度 - ØID = 贯通孔