

# SRS AS 30-100

单管卡圈用六角螺钉

**HANSA FLEX**

## 属性

|      |   |
|------|---|
| 结构类型 | 单管卡圈用                                   |
| 结构系列 | 重                                       |
| 标准   | DIN 931 (ISO 4014) 或 DIN 933 (ISO 4017) |
| 原料   | 钢                                       |
| 表面保护 | 电镀涂层                                    |



## 货品

| 名称         | 卡圈大小 | G    | L<br>(mm) | SW<br>(mm) |
|------------|------|------|-----------|------------|
| SRS AS 30  | 1    | M 10 | 40        | 17         |
| SRS AS 40  | 2    | M 10 | 60        | 17         |
| SRS AS 50  | 3    | M 10 | 70        | 17         |
| SRS AS 60  | 4    | M 12 | 100       | 19         |
| SRS AS 70  | 5    | M 16 | 130       | 24         |
| SRS AS 80  | 6    | M 20 | 190       | 30         |
| SRS AS 90  | 7    | M 24 | 220       | 36         |
| SRS AS 100 | 8    | M 30 | 300       | 46         |

## 产品变体

SRS AS 30-100 V4 单管卡圈用六角螺钉, 不锈钢 1.4571

## 是以下产品的附加元件

|     |         |
|-----|---------|
| C D | C类组装 双重 |
| C   | C类组装    |