


属性

应用范围	冷却水软管
特殊的属性	耐受温度范围广泛 耐受各种冷却油,油类及清洁剂 耐臭氧,耐紫外线,耐老化 硅胶的柔软性使安装非常容易
标准	符合:SAE 20 R3
内胶层	蓝色硅胶
增强层	织物衬里
外胶层	蓝色硅胶
颜色	蓝色
温度范围	水 + 防冻剂 -50 °C 至 +150 °C 热空气 + 180 °C
适用介质	冷却液 热空气



货品

名称	内径-Ø (mm)	外径Ø (mm)	破裂压力 (bar)	卷长 (m)
KUEHLER 08-4 SBL	8	16	24	1 / 10 / 20
KUEHLER 10-4 SBL	10	18	24	1 / 10 / 20
KUEHLER 12-4 SBL	12	20	24	1 / 10 / 20
KUEHLER 14-4 SBL	14	22	20	1 / 10 / 20
KUEHLER 16-4 SBL	16	24	18	1 / 10 / 20
KUEHLER 18-4 SBL	18	26	18	1 / 10 / 20
KUEHLER 20-4 SBL	20	28	14	1 / 10 / 20
KUEHLER 22-4 SBL	22	30	14	1 / 10 / 20
KUEHLER 25-4.5 SBL	25	34	14	1 / 10 / 20
KUEHLER 28-4.5 SBL	28	37	14	1 / 10 / 20
KUEHLER 30-4.5 SBL	30	39	14	1
KUEHLER 32-4.5 SBL	32	41	12	1
KUEHLER 35-4.5 SBL	35	44	12	1
KUEHLER 38-4.5 SBL	38	47	10	1
KUEHLER 40-4.5 SBL	40	49	10	1
KUEHLER 45-4.5 SBL	45	54	10	1
KUEHLER 48-5.5 SBL	48	59	8	1
KUEHLER 50-4.5 SBL	50	59	8	1
KUEHLER 57-4.5 SBL	57	66	8	1
KUEHLER 60-4.5 SBL	60	69	8	1
KUEHLER 65-5.5 SBL	65	76	8	1
KUEHLER 70-5.5 SBL	70	81	8	1
KUEHLER 80-6 SBL	80	92	8	1