


属性

| | |
|-------|---|
| 应用范围 | 冷却水软管 |
| 特殊的属性 | 耐受温度范围广泛 耐受各种冷却油,油类及清洁剂 耐臭氧,耐紫外线,耐老化 硅胶的柔软性使安装非常容易 |
| 标准 | 符合:SAE 20 R3 |
| 内胶层 | 蓝色硅胶 |
| 增强层 | 织物衬里 |
| 外胶层 | 蓝色硅胶 |
| 颜色 | 蓝色 |
| 温度范围 | 水 + 防冻剂 -50 °C 至 +150 °C 热空气 + 180 °C |
| 适用介质 | 冷却液 热空气 |



货品

| 名称 | 内径-Ø (mm) | 外径Ø (mm) | 破裂压力 (bar) | 卷长 (m) |
|--------------------|--------------|-------------|---------------|-------------|
| KUEHLER 08-4 SBL | 8 | 16 | 24 | 1 / 10 / 20 |
| KUEHLER 10-4 SBL | 10 | 18 | 24 | 1 / 10 / 20 |
| KUEHLER 12-4 SBL | 12 | 20 | 24 | 1 / 10 / 20 |
| KUEHLER 14-4 SBL | 14 | 22 | 20 | 1 / 10 / 20 |
| KUEHLER 16-4 SBL | 16 | 24 | 18 | 1 / 10 / 20 |
| KUEHLER 18-4 SBL | 18 | 26 | 18 | 1 / 10 / 20 |
| KUEHLER 20-4 SBL | 20 | 28 | 14 | 1 / 10 / 20 |
| KUEHLER 22-4 SBL | 22 | 30 | 14 | 1 / 10 / 20 |
| KUEHLER 25-4.5 SBL | 25 | 34 | 14 | 1 / 10 / 20 |
| KUEHLER 28-4.5 SBL | 28 | 37 | 14 | 1 / 10 / 20 |
| KUEHLER 30-4.5 SBL | 30 | 39 | 14 | 1 |
| KUEHLER 32-4.5 SBL | 32 | 41 | 12 | 1 |
| KUEHLER 35-4.5 SBL | 35 | 44 | 12 | 1 |
| KUEHLER 38-4.5 SBL | 38 | 47 | 10 | 1 |
| KUEHLER 40-4.5 SBL | 40 | 49 | 10 | 1 |
| KUEHLER 45-4.5 SBL | 45 | 54 | 10 | 1 |
| KUEHLER 48-5.5 SBL | 48 | 59 | 8 | 1 |
| KUEHLER 50-4.5 SBL | 50 | 59 | 8 | 1 |
| KUEHLER 57-4.5 SBL | 57 | 66 | 8 | 1 |
| KUEHLER 60-4.5 SBL | 60 | 69 | 8 | 1 |
| KUEHLER 65-5.5 SBL | 65 | 76 | 8 | 1 |
| KUEHLER 70-5.5 SBL | 70 | 81 | 8 | 1 |
| KUEHLER 80-6 SBL | 80 | 92 | 8 | 1 |