

属性	
接口 1	接合器父部件
接口2	BSP外螺纹,圆柱形
原料	钢
表面保护	火焰镀锌



货品					
名称	工作压力	接合器尺寸	G1		
	(bar)	(mm)			
PRT S 50 HR 1.1/2	25,0	50,0	G 1.1/2" -11		
PRT S 50 HR 2	25,0	50,0	G 2" -11		
PRT S 70 HR 2	25,0	70,0	G 2" -11		
PRT S 70 HR 2.1/2	25,0	70,0	G 2.1/2" -11		
PRT S 70 HR 3	25,0	70,0	G 3" -11		
PRT S 89 HR 2.1/2	25,0	89,0	G 2.1/2" -11		
PRT S 89 HR 3	25,0	89,0	G 3" -11		
PRT S 108 HR 2.1/2	25,0	108,0	G 2.1/2" -11		
PRT S 108 HR 3	25,0	108,0	G 3" -11		
PRT S 108 HR 4	25,0	108,0	G 4" -11		
PRT S 133 HR 2.1/2	25,0	133,0	G 2.1/2" -11		
PRT S 133 HR 4	25,0	133,0	G 4" -11		
PRT S 133 HR 5	25,0	133,0	G 5" -11		
PRT S 159 HR 2.1/2	25,0	159,0	G 2.1/2" -11		
PRT S 159 HR 4	25,0	159,0	G 4" -11		
PRT S 159 HR 6	25,0	159,0	G 6" -11		