

PRT S HR

Perrot接合器 父部件外螺纹

属性

| | |
|------|------------|
| 接口 1 | 接合器父部件 |
| 接口 2 | BSP外螺纹,圆柱形 |
| 原料 | 钢 |
| 表面保护 | 火焰镀锌 |



货品

| 名称 | 工作压力 (bar) | 接合器尺寸 (mm) | G1 |
|--------------------|---------------|---------------|--------------|
| PRT S 50 HR 1.1/2 | 25,0 | 50,0 | G 1.1/2" -11 |
| PRT S 50 HR 2 | 25,0 | 50,0 | G 2" -11 |
| PRT S 70 HR 2 | 25,0 | 70,0 | G 2" -11 |
| PRT S 70 HR 2.1/2 | 25,0 | 70,0 | G 2.1/2" -11 |
| PRT S 70 HR 3 | 25,0 | 70,0 | G 3" -11 |
| PRT S 89 HR 2.1/2 | 25,0 | 89,0 | G 2.1/2" -11 |
| PRT S 89 HR 3 | 25,0 | 89,0 | G 3" -11 |
| PRT S 108 HR 2.1/2 | 25,0 | 108,0 | G 2.1/2" -11 |
| PRT S 108 HR 3 | 25,0 | 108,0 | G 3" -11 |
| PRT S 108 HR 4 | 25,0 | 108,0 | G 4" -11 |
| PRT S 133 HR 2.1/2 | 25,0 | 133,0 | G 2.1/2" -11 |
| PRT S 133 HR 4 | 25,0 | 133,0 | G 4" -11 |
| PRT S 133 HR 5 | 25,0 | 133,0 | G 5" -11 |
| PRT S 159 HR 2.1/2 | 25,0 | 159,0 | G 2.1/2" -11 |
| PRT S 159 HR 4 | 25,0 | 159,0 | G 4" -11 |
| PRT S 159 HR 6 | 25,0 | 159,0 | G 6" -11 |