

# PRT M HR

## Perrot接合器母部件外螺纹

### 属性

接口 1	接合器母部件
密封形式 1	O形圈密封式
接口 2	BSP外螺纹,圆柱形
原料	钢
表面保护	火焰镀锌



### 货品

名称	工作压力 (bar)	接合器尺寸 (mm)	G1
PRT M 50 HR 1.1/2	12,0	50,0	G 1.1/2" -11
PRT M 50 HR 2	12,0	50,0	G 2"
PRT M 50 HR 2.1/2	12,0	50,0	G 2.1/2" -11
PRT M 70 HR 2	12,0	70,0	G 2"
PRT M 70 HR 2.1/2	12,0	70,0	G 2.1/2" -11
PRT M 70 HR 3	12,0	70,0	G 3" -11
PRT M 89 HR 2.1/2	12,0	89,0	G 2.1/2" -11
PRT M 89 HR 3	12,0	89,0	G 3" -11
PRT M 108 HR 2.1/2	12,0	108,0	G 2.1/2" -11
PRT M 108 HR 3	12,0	108,0	G 3" -11
PRT M 108 HR 4	12,0	108,0	G 4" -11
PRT M 133 HR 2.1/2	12,0	133,0	G 2.1/2" -11
PRT M 133 HR 4	12,0	133,0	G 4" -11
PRT M 133 HR 5	12,0	133,0	G 5" -11
PRT M 159 HR 2.1/2	12,0	159,0	G 2.1/2" -11
PRT M 159 HR 4	12,0	159,0	G 4" -11
PRT M 159 HR 6	12,0	159,0	G 6" -11