


属性	
接口1	米制外螺纹,圆柱形
密封形式 1	24°内锥
接口 2	米制外螺纹,圆柱形
密封形式 2	24°内锥
结构类型	旋转螺栓连接
结构形式	双角90°
供货范围	接套(不带锁紧螺母和切割环)
原料	钢
表面保护	电镀涂层





提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品	
夕称	

结构系列	工作压力 巴	Ø d2	G1	L1	L2	L3	L4	L6	SW
		(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
S	PN 400	12	M 20 x 1.5	28	20,5	28	20,5	32	32
S	PN 400	16	M 24 x 1.5	34	25,5	34	25,5	40	40
S	PN 250	20	M 30 x 2	38	27,5	38	27,5	45	45
S	PN 250	25	M 36 x 2	45	33,0	45	33,0	55	55
S	PN 250	30	M 42 x 2	52	38,5	52	38,5	65	65
S	PN 250	38	M 52 x 2	59	43,0	59	43,0	75	75
	S S S S	S PN 400 S PN 400 S PN 250 S PN 250 S PN 250	S PN 400 12 S PN 400 16 S PN 250 20 S PN 250 25 S PN 250 30	S PN 400 12 M 20 x 1.5 S PN 400 16 M 24 x 1.5 S PN 250 20 M 30 x 2 S PN 250 25 M 36 x 2 S PN 250 30 M 42 x 2	(mm) (mm) S PN 400 12 M 20 x 1.5 28 S PN 400 16 M 24 x 1.5 34 S PN 250 20 M 30 x 2 38 S PN 250 25 M 36 x 2 45 S PN 250 30 M 42 x 2 52	Key Common (mm) (mm) (mm) (mm) S PN 400 12 M 20 x 1.5 28 20,5 S PN 400 16 M 24 x 1.5 34 25,5 S PN 250 20 M 30 x 2 38 27,5 S PN 250 25 M 36 x 2 45 33,0 S PN 250 30 M 42 x 2 52 38,5	Key Computer (mm) (mm) (mm) (mm) S PN 400 12 M 20 x 1.5 28 20,5 28 S PN 400 16 M 24 x 1.5 34 25,5 34 S PN 250 20 M 30 x 2 38 27,5 38 S PN 250 25 M 36 x 2 45 33,0 45 S PN 250 30 M 42 x 2 52 38,5 52	S PN 400 12 M 20 x 1.5 28 20,5 28 20,5 S PN 400 16 M 24 x 1.5 34 25,5 34 25,5 S PN 250 20 M 30 x 2 38 27,5 38 27,5 S PN 250 25 M 36 x 2 45 33,0 45 33,0 S PN 250 30 M 42 x 2 52 38,5 52 38,5	Key Computer (mm) (mm)