

## 属性

应用范围	高压水清洗设备和排水设备 工业
特殊的属性	特别抗磨损的表层 耐气候
接口 1	BSP螺母螺纹
接口 2	BSP外螺纹,圆柱形
内胶层	SBR
增强层	两层高强度合成纤维编织
外胶层	丁苯橡胶NR/BR, 光滑表面
颜色	黑色
温度 min.	-35 °C
温度 max.	80 °C
适用介质	水

## 货品

名称	DN*	尺寸	英寸	内径-Ø (mm)	外径Ø (mm)	工作压力 (bar)	最小弯曲半径 (mm)	长度 (m)
KANA 13X040M AB HB	12	8	1/2"	13	25	250,0	70	40,00
KANA 13X060M AB HB	12	8	1/2"	13	25	250,0	70	60,00
KANA 13X080M AB HB	12	8	1/2"	13	25	250,0	70	80,00
KANA 13X120M AB HB	12	8	1/2"	13	25	250,0	70	120,00
KANA 13X160M AB HB	12	8	1/2"	13	25	250,0	70	160,00
KANA 13X180M AB HB	12	8	1/2"	13	25	250,0	70	180,00
KANA 13X200M AB HB	12	8	1/2"	13	25	250,0	70	200,00
KANA 20X040M AB HB	19	12	3/4"	19	31	250,0	95	40,00
KANA 20X060M AB HB	19	12	3/4"	19	31	250,0	95	60,00
KANA 20X080M AB HB	19	12	3/4"	19	31	250,0	95	80,00
KANA 20X120M AB HB	19	12	3/4"	19	31	250,0	95	120,00
KANA 20X160M AB HB	19	12	3/4"	19	31	250,0	95	160,00
KANA 20X180M AB HB	19	12	3/4"	19	31	250,0	95	180,00
KANA 20X200M AB HB	19	12	3/4"	19	31	250,0	95	200,00
KANA 25X040M AB HB	25	16	1"	25	39	250,0	110	40,00
KANA 25X060M AB HB	25	16	1"	25	39	250,0	110	60,00
KANA 25X080M AB HB	25	16	1"	25	39	250,0	110	80,00
KANA 25X120M AB HB	25	16	1"	25	39	250,0	110	120,00
KANA 25X160M AB HB	25	16	1"	25	39	250,0	110	160,00
KANA 25X180M AB HB	25	16	1"	25	39	250,0	110	180,00
KANA 25X200M AB HB	25	16	1"	25	39	250,0	110	200,00
KANA 25X240M AB HB	25	16	1"	25	39	250,0	110	240,00
KANA 32X040M AB HB	31	20	1.1/4"	32	48	250,0	150	40,00
KANA 32X060M AB HB	31	20	1.1/4"	32	48	250,0	150	60,00
KANA 32X080M AB HB	31	20	1.1/4"	32	48	250,0	150	80,00
KANA 32X120M AB HB	31	20	1.1/4"	32	48	250,0	150	120,00
KANA 32X160M AB HB	31	20	1.1/4"	32	48	250,0	150	160,00
KANA 32X180M AB HB	31	20	1.1/4"	32	48	250,0	150	180,00
KANA 32X200M AB HB	31	20	1.1/4"	32	48	250,0	150	200,00