

AFS SRE (6000 PSI)

SAE焊接环

HANSA FLEX

属性

| | |
|------|-------------------------|
| 压力系列 | 6000 psi |
| 标准 | SAE J 518 C ISO 6162 |
| 结构形式 | 直道 |
| 结构类型 | SAE焊接束 |
| 固定 | 螺钉钻孔 |
| 供货范围 | 仅法兰 |
| 原料 | S355J2G3 (ST52.3) |
| 表面保护 | 经黑色润滑油处理 |



提示

给出的最大工作压力针对的是法兰!实际工作压力视管(壁厚)和管的品质而定!
推荐使用的螺钉在M(米制)或M(unc)列中列出。

货品

| 名称 | PB 10.9 (bar) | 结构尺 寸 | 管 | A (mm) | B1 (mm) | B2 (mm) | G (mm) | C (mm) | E (mm) | H (mm) | L (mm) | M 米制 | M unc |
|----------------|------------------|----------|-------------|-----------|------------|------------|-----------|-----------|-----------|-----------|-----------|-----------|----------------|
| AFS 401 SRE 20 | 400 | 1/2" | 20 x 3 | 20 | 14,0 | 14 | 34,0 | 40,5 | 18,2 | 16,0 | 9,0 | M 8 x 30 | 5/16" x 1.1/4" |
| AFS 402 SRE 20 | 400 | 3/4" | 20 x 3 | 20 | 14,0 | 14 | 35,0 | 50,8 | 23,8 | 21,0 | 11,0 | M 10 x 35 | 3/8" x 1.1/2" |
| AFS 402 SRE 25 | 400 | 3/4" | 25 x 4 | 25 | 17,0 | 17 | 35,0 | 50,8 | 23,8 | 21,0 | 11,0 | M 10 x 35 | 3/8" x 1.1/2" |
| AFS 403 SRE 25 | 400 | 1" | 25 x 4 | 25 | 17,0 | 17 | 42,0 | 57,2 | 27,8 | 25,0 | 13,0 | M 12 x 45 | 7/16" x 1.1/2" |
| AFS 403 SRE 30 | 400 | 1" | 30 x 4 | 30 | 22,0 | 22 | 42,0 | 57,2 | 27,8 | 25,0 | 13,0 | M 12 x 45 | 7/16" x 1.1/2" |
| AFS 404 SRE 30 | 400 | 1.1/4" | 30 x 4 | 30 | 22,0 | 22 | 44,0 | 66,7 | 31,8 | 25,0 | 15,0 | M 14 x 50 | 1/2" x 1.3/4" |
| AFS 404 SRE 38 | 400 | 1.1/4" | 38 x 6 | 38 | 26,0 | 26 | 44,0 | 66,7 | 31,8 | 25,0 | 15,0 | M 14 x 50 | 1/2" x 1.3/4" |
| AFS 405 SRE 38 | 400 | 1.1/2" | 38 x 6 | 38 | 26,0 | 26 | 56,0 | 49,4 | 36,5 | 28,0 | 17,0 | M 16 x 50 | 5/8" x 2" |
| AFS 405 SRE 48 | 400 | 1.1/2" | 48.3 x 8 | 49 | 32,0 | 32 | 56,0 | 79,4 | 36,5 | 28,0 | 17,0 | M 16 x 50 | 5/8" x 2" |
| AFS 405 SRE 60 | 400 | 1.1/2" | 60.3 x 10 | 61 | 40,0 | 40 | 56,0 | 79,4 | 36,5 | 27,0 | 17,0 | M 16 x 50 | 5/8" x 2" |
| AFS 406 SRE 60 | 400 | 2" | 60.3 x 10 | 61 | 40,0 | 40 | 65,0 | 96,8 | 44,5 | 37,0 | 21,0 | M 20 x 70 | 3/4" x 2.1/2" |
| AFS 406 SRE 76 | 400 | 2" | 76.1 x 12.5 | 76 | 50,0 | 48 | 80,0 | 96,8 | 44,5 | 33,0 | 21,0 | M 20 x 65 | 3/4" x 2.1/2" |

PN = 额定压力 PB = 最大工作压力

产品变体

| | |
|-----------------------------|------------------------|
| AFS SRE M (3000 / 6000 PSI) | SAE焊接环, 带米制螺钉组件和O形圈 |
| AFS SRE U (3000 / 6000 PSI) | SAE焊接环, 带UNC标准螺钉组件和O形圈 |