

# K-PVDF-SCHLAUCH NATUR

PVDF tubing nature

**HANSA FLEX**

## 属性

应用 resistant to a variety of chemicals


内胶层 PVDF

外胶层 PVDF

颜色 Natural

温度 min. -40 °C

温度 max. 150 °C



## 附加信息

- very good temperature resistance
- extremely high pressure resistance
- sterilisable
- non-combustible (to UL 94 V-O)
- very good UV resistance
- very low gas permeability
- excellent mechanical properties

## 货品

| 名称             | 内径-Ø<br>(mm) | 外径Ø<br>(mm) | 壁厚<br>(mm) | 最小弯曲半径<br>(mm) | 卷长<br>(m) |
|----------------|--------------|-------------|------------|----------------|-----------|
| K- 07 10 13 16 | 2,0          | 4,0         | 1,0        | 60             | 100       |
| K- 07 10 13 17 | 4,0          | 6,0         | 1,0        | 75             | 100       |
| K- 07 10 13 18 | 6,0          | 8,0         | 1,0        | 85             | 100       |
| K- 07 10 13 19 | 8,0          | 10,0        | 1,0        | 100            | 100       |
| K- 07 10 13 20 | 10,0         | 12,0        | 1,0        | 125            | 100       |