

属性

接口 1 + 2 米制外螺纹,圆柱形

标准 tested in accordance with
 DIN 74323
 DIN 74324
 ISO 7268-2
 ISO 7375-2
 DIN 73378
 DIN 74310-2

许可 German Technical Surveyance Association (TÜV)-type
 approved (Certificate R 9910199)

温度 min. -40 °C

温度 max. 90 °C

原料 PUR



附加信息

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

货品

名称	G1 - G2	内径-Ø (mm)	外径Ø (mm)	壁厚 (mm)	长度 (m)	颜色
K-07 10 13 21	M 16 x 1.5	8,0	12,0	2,0	4,50	黑色
K-07 10 13 22	M 16 x 1.5	8,0	12,0	2,0	4,50	黄色
K-07 10 13 23	M 16 x 1.5	8,0	12,0	2,0	4,50	红色
K-07 10 13 24	M 16 x 1.5	8,0	12,0	2,0	5,50	黑色
K-07 10 13 25	M 16 x 1.5	8,0	12,0	2,0	5,50	黄色
K-07 10 13 26	M 16 x 1.5	8,0	12,0	2,0	5,50	红色