# K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA-FLEX

## 属性

| | |
|---|---|
| **接口 1 + 2** | 米制外螺纹,圆柱形 |
| **标准** | tested in accordance with<br>DIN 74323<br>DIN 74324<br>ISO 7268-2<br>ISO 7375-2<br>DIN 73378<br>DIN 74310-2 |
| **许可** | German Technical Surveyance Association (TÜV)-type upproved (Certificate R 9910199) |
| **温度 min.** | -40 °C |
| **温度 max.** | 90 °C |
| **原料** | PUR |



## 附加信息

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## 货品

| 名称 | G1 - G2 | 内径-Ø (mm) | 外径Ø (mm) | 壁厚 (mm) | 长度 (m) | 颜色 |
|---|---|---|---|---|---|---|
| **K- 07 10 13 21** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 4,50 | 黑色 |
| **K- 07 10 13 22** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 4,50 | 黄色 |
| **K- 07 10 13 23** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 4,50 | 红色 |
| **K- 07 10 13 24** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 5,50 | 黑色 |
| **K- 07 10 13 25** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 5,50 | 黄色 |
| **K- 07 10 13 26** | M 16 x 1.5 | 8,0 | 12,0 | 2,0 | 5,50 | 红色 |

*尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。*