K-PUR-BREMSSPIRALE

PUR brake coil with connection



属性	
接口 1 + 2	米制外螺纹,圆柱形
标准	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
许可	German Technical Surveyance Association (TÜV)-type upproved (Certificate R 9910199)
温度 min.	-40 °C
温度 max.	90 °C
原料	PUR



附加信息

- will not break at fittings
- excellent antikink characteristics kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than

conventional coil tubing

货品						
名称	G1 - G2	内径-Ø _(mm)	外径Ø (mm)	壁厚 (mm)	长度 (m)	颜色
K- 07 10 13 21	M 16 x 1.5	8,0	12,0	2,0	4,50	黑色
K- 07 10 13 22	M 16 x 1.5	8,0	12,0	2,0	4,50	黄色
K- 07 10 13 23	M 16 x 1.5	8,0	12,0	2,0	4,50	红色
K- 07 10 13 24	M 16 x 1.5	8,0	12,0	2,0	5,50	黑色
K- 07 10 13 25	M 16 x 1.5	8,0	12,0	2,0	5,50	黄色
K- 07 10 13 26	M 16 x 1.5	8,0	12,0	2,0	5,50	红色