

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

属性

接口 1 + 2	米制外螺纹,圆柱形
标准	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
许可	German Technical Surveyance Association (TÜV)-type approved (Certificate R 9910199)
温度 min.	-40 °C
温度 max.	90 °C
原料	PUR



附加信息

- will not break at fittings
 - excellent antikink characteristics – kinking
- leaves no defects
- longer operation length
 - highly resistant to tearing off at fittings
 - excellent springback characteristics
 - unplasticized so no embrittlement
 - resistant to oil and grease
 - resistant to UV and ozon
 - service life many times longer than
conventional coil tubing

货品

名称	G1 - G2	内径-Ø (mm)	外径Ø (mm)	壁厚 (mm)	长度 (m)	颜色
K- 07 10 13 21	M 16 x 1.5	8,0	12,0	2,0	4,50	黑色
K- 07 10 13 22	M 16 x 1.5	8,0	12,0	2,0	4,50	黄色
K- 07 10 13 23	M 16 x 1.5	8,0	12,0	2,0	4,50	红色
K- 07 10 13 24	M 16 x 1.5	8,0	12,0	2,0	5,50	黑色
K- 07 10 13 25	M 16 x 1.5	8,0	12,0	2,0	5,50	黄色
K- 07 10 13 26	M 16 x 1.5	8,0	12,0	2,0	5,50	红色