

# K-BIMETALLTHERMOMETER 46

Bimetallic thermometers

**HANSA FLEX**

## 属性

类型	46
显示修正	On end of stem
工作压力	Max. 6 bar (on thermowell)
防护管	Clamped (removable), copper alloy
壳体	Plastic
密封片	Plexiglass



## 提示

其它数据应客户要求提供。

## 描述

Applications: Heating, plumbing, universal.

## 货品

名称	显示范围	Ø (mm)	潜杆长度	螺纹
K- 07 20 09 86	0 °C to +60 °C	63,0	40 mm	G 1/2
K- 07 20 09 87	0 °C to +120 °C	63,0	40 mm	G 1/2
K- 07 20 09 88	0 °C to +60 °C	63,0	60 mm	G 1/2
K- 07 20 09 89	0 °C to +120 °C	63,0	60 mm	G 1/2
K- 07 20 09 90	0 °C to +60 °C	63,0	100 mm	G 1/2
K- 07 20 09 91	0 °C to +120 °C	63,0	100 mm	G 1/2
K- 07 20 10 19	0 °C to +60 °C	80,0	40 mm	G 1/2
K- 07 20 10 20	0 °C to +120 °C	80,0	40 mm	G 1/2
K- 07 20 10 21	0 °C to +60 °C	80,0	60 mm	G 1/2
K- 07 20 10 22	0 °C to +120 °C	80,0	60 mm	G 1/2
K- 07 20 10 23	0 °C to +60 °C	80,0	100 mm	G 1/2
K- 07 20 10 24	0 °C to +120 °C	80,0	100 mm	G 1/2