

K-DMUF GENAUIGKEIT 0,2%

Pressure transmitters, accuracy 0.2% of span

HANSA FLEX

属性

| | |
|-----------|--|
| 类型 | S-10 |
| 电压 | Non-stabilised 10/30 V DC voltage |
| 电接口 | With right-angle connector acc. to DIN EN 175301-803 A |
| 保护等级 | IP 65 acc. to EN 60529 |
| 输出信号 | 4 to 20 mA, 2-wire |
| 非线性 | 0.2% of span |
| 介质温度 | -30 °C to +100 °C |
| 环境温度 | -20 °C to +80 °C |
| 测量材料触碰的零件 | CrNi steel 1.4571 |
| 壳体 | CrNi steel 1.4571 |



描述

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

附加信息

Further measuring ranges on request

Pressure converter with flush-mounted membrane for measuring highly viscous and crystalline media on request.

货品

| 名称 | 测量范围 | 螺纹 |
|----------------|---------------|-------|
| K- 07 20 10 30 | -1 / 0.0 bar | G 1/2 |
| K- 07 20 10 31 | 0 - 0.25 bar | G 1/2 |
| K- 07 20 10 32 | 0 - 0.4 bar | G 1/2 |
| K- 07 20 10 33 | 0 - 1.0 bar | G 1/2 |
| K- 07 20 10 34 | 0 - 4.0 bar | G 1/2 |
| K- 07 20 10 35 | 0 - 6.0 bar | G 1/2 |
| K- 07 20 10 36 | 0 - 10.0 bar | G 1/2 |
| K- 07 20 10 37 | 0 - 16.0 bar | G 1/2 |
| K- 07 20 10 38 | 0 - 25.0 bar | G 1/2 |
| K- 07 20 10 39 | 0 - 40.0 bar | G 1/2 |
| K- 07 20 10 40 | 0 - 60.0 bar | G 1/2 |
| K- 07 20 10 41 | 0 - 100.0 bar | G 1/2 |
| K- 07 20 10 42 | 0 - 160.0 bar | G 1/2 |
| K- 07 20 10 43 | 0 - 250.0 bar | G 1/2 |
| K- 07 20 10 44 | 0 - 400.0 bar | G 1/2 |
| K- 07 20 10 45 | 0 - 600.0 bar | G 1/2 |