

K-MANO U

Pressure gauges (CrNi steel type / connection radial on bottom)

HANSA FLEX

属性	
类型	232.50
规格	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
应用	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
质量等级	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
介质温度	max. +200 °C
环境温度	-40 °C to +60 °C
壳体	CrNi steel
密封片	Laminated safety glass Ø 63 = Polycarbonate



提示

其它数据应客户要求提供。

货品

名称	测量范围	Ø (mm)	接口
K- 07 20 06 01	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 02	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 03	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 04	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 05	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 06	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 07	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 08	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 09	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 00 36	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 00 37	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 00 38	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 00 39	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 00 40	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 00 41	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 00 42	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 00 43	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 44	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 45	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 46	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 47	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 48	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 00 49	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 00 50	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 00 51	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 00 52	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 03 10	-1 / 0.0 bar	160,0	G 1/2"
K- 07 20 03 11	-1 / +0.6 bar	160,0	G 1/2"
K- 07 20 03 12	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 13	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 14	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 15	0 - 25.0 bar	160,0	G 1/2"