

K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

HANSA FLEX

属性

| | |
|------|---|
| 类型 | 232.30 |
| 规格 | Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing) |
| 应用 | For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere |
| 质量等级 | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm) |
| 介质温度 | max. +200 °C |
| 环境温度 | -40 °C to +60 °C |
| 壳体 | CrNi steel |
| 密封片 | Laminated safety glass Ø 63 = Polycarbonate |



提示

其它数据应客户要求提供。

描述

Safety version with more fracture-resistant separating wall

货品

| 名称 | 测量范围 | Ø (mm) | 接口 |
|----------------|---------------|-----------|--------|
| K- 07 20 07 15 | -1 / 0.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 16 | 0 - 1.6 bar | 63,0 | G 1/4" |
| K- 07 20 07 17 | 0 - 2.5 bar | 63,0 | G 1/4" |
| K- 07 20 07 18 | 0 - 4.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 19 | 0 - 6.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 20 | 0 - 10.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 21 | 0 - 16.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 22 | 0 - 25.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 23 | 0 - 40.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 24 | 0 - 60.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 25 | 0 - 100.0 bar | 63,0 | G 1/4" |
| K- 07 20 01 97 | 0 - 1.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 98 | 0 - 1.6 bar | 100,0 | G 1/2" |
| K- 07 20 01 99 | 0 - 2.5 bar | 100,0 | G 1/2" |
| K- 07 20 02 00 | 0 - 4.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 01 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 02 | 0 - 10.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 03 | 0 - 16.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 04 | 0 - 25.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 05 | 0 - 40.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 06 | 0 - 60.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 07 | 0 - 100.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 08 | 0 - 160.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 09 | 0 - 250.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 10 | 0 - 400.0 bar | 100,0 | G 1/2" |