

K-MANO ROB H

Robust pressure gauges, connection on rear, eccentric

HANSA FLEX

属性	
类型	212.20
规格	Robust Bourdon-tube pressure gauge
应用	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
质量等级	1,0
介质温度	max. +80 °C
环境温度	-40 °C to +60 °C
壳体	CrNi steel
测量组件	Copper alloy (≤ 100 bar), CrNi steel (> 100 bar)
密封片	Flat instrument glass
拨针机构	Copper alloy



提示

其它数据应客户要求提供。

附加信息

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

货品

名称	测量范围	Ø (mm)	接口
K- 07 20 01 67	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 68	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 69	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 70	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 71	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 72	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 73	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 74	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 75	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 76	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 77	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 78	0 - 250.0 bar	100,0	G 1/2"