K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male



属性	
应用	For all pressure gauges with a flat gasket acc. to DIN 16258
压力范围	Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures
温度	Max. +50 °C
売体	Brass with a bare metal surface or stainless steel 1.4571
手柄	Plastic
检查法兰	-



提示

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B

K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

其它数据应客户要求提供。

描述

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

附加信息

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

货品						
名称	螺纹	PN (bar)	SW	原料		
K- 07 20 10 94	G 1/4	6	(mm) 17			
K- 07 20 10 95	G 3/8	16	22			
K- 07 20 10 97	G 1/2	25	27	黄铜		
K- 07 20 10 96	G 1/2	25	27	Stainless steel		
K- 07 20 10 98	G 1/2	25	27	黄铜		