

# K-RMM HFR STAHLBLECH SCHW

Standard pressure gauges with black sheet-steel bezel, connection on rear

**HANSA FLEX**

<b>属性</b>	
类型	111.12
规格	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
应用	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
质量等级	1,6
介质温度	最大 +60 °C
环境温度	-20 °C 至 +60 °C
壳体	Sheet steel
测量组件和拨针机构的材料	铜合金
密封片	Transparent plastic



## 提示

其它数据应客户要求提供。

## 货品

名称	测量范围	Ø (mm)	接口
K- 07 20 04 27	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 28	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 29	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 30	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 31	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 32	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 33	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 34	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 35	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 36	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 30	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 31	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 32	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 33	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 34	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 35	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 36	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 37	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 38	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 39	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 40	0 - 60.0 bar	50,0	G 1/4