K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

属性

工作温度	-60 °C to +100 °C (PA 12)
属性	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
原料	Polyamid PA 12, hard (according to DIN 73378)



提示

Operating pressure with 2.5 x overpressure safety!
其它数据应客户要求提供。

描述

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

货品

名称	软管内径 Ø (mm)	软管外径 Ø (mm)	20 摄氏度时的最大操作压力 (bar)	卷长 (m)
K- 07 10 04 77	9,0	12,0	19	25
K- 07 10 04 79	12,0	15,0	15	25
K- 07 10 04 81	14,0	18,0	16	25
K- 07 10 04 83	18,0	22,0	14	25
K- 07 10 04 76	9,0	12,0	19	100
K- 07 10 04 78	12,0	15,0	15	100
K- 07 10 04 80	14,0	18,0	16	100
K- 07 10 04 82	18,0	22,0	14	100
K- 07 10 04 84	23,0	28,0	14	50

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。