

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

属性

| | |
|------|---|
| 工作温度 | -60 °C to +100 °C (PA 12) |
| 属性 | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| 管长度 | 3 m |
| 包装单元 | 10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units! |
| 原料 | Polyamid PA 12, hard (according to DIN 73378) |



提示

Operating pressure with 2.5 x overpressure safety!

其它数据应客户要求提供。

描述

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

货品

| 名称 | 管外径 Ø (mm) | 管内径 Ø (mm) | 20 摄氏度时的最大操作压力 (bar) | 颜色 |
|----------------|---------------|---------------|-------------------------|----|
| K- 07 10 04 57 | 12 | 9 | 38 | 蓝色 |
| K- 07 10 04 59 | 12 | 9 | 38 | 黑色 |
| K- 07 10 04 61 | 15 | 12 | 25 | 蓝色 |
| K- 07 10 04 63 | 15 | 12 | 25 | 黑色 |
| K- 07 10 04 65 | 18 | 14 | 28 | 蓝色 |
| K- 07 10 04 67 | 18 | 14 | 28 | 黑色 |
| K- 07 10 04 69 | 22 | 18 | 22 | 蓝色 |
| K- 07 10 04 71 | 22 | 18 | 22 | 黑色 |
| K- 07 10 04 73 | 28 | 23 | 20 | 蓝色 |
| K- 07 10 04 75 | 28 | 23 | 20 | 黑色 |