

# K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

**HANSA FLEX**

## 属性

工作温度	-60 °C to +100 °C (PA 12)
属性	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
管长度	3 m
包装单元	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
原料	Polyamid PA 12, hard (according to DIN 73378)



## 提示

Operating pressure with 2.5 x overpressure safety!

其它数据应客户要求提供。

## 描述

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## 货品

名称	管外径 Ø (mm)	管内径 Ø (mm)	20 摄氏度时的最大操作压力 (bar)	颜色
K- 07 10 04 57	12	9	38	蓝色
K- 07 10 04 59	12	9	38	黑色
K- 07 10 04 61	15	12	25	蓝色
K- 07 10 04 63	15	12	25	黑色
K- 07 10 04 65	18	14	28	蓝色
K- 07 10 04 67	18	14	28	黑色
K- 07 10 04 69	22	18	22	蓝色
K- 07 10 04 71	22	18	22	黑色
K- 07 10 04 73	28	23	20	蓝色
K- 07 10 04 75	28	23	20	黑色