K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

属性

工作温度	-60 °C to +100 °C (PA 12)
属性	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
管长度	3 m
包装单元	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
原料	Polyamid PA 12, hard (according to DIN 73378)



提示

Operating pressure with 2.5 x overpressure safety!
其它数据应客户要求提供。

描述

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

货品

名称	管外径 Ø (mm)	管内径 Ø (mm)	20 摄氏度时的最大操作压力 (bar)	颜色
K- 07 10 04 56	12	9	38	蓝色
K- 07 10 04 58	12	9	38	黑色
K- 07 10 04 60	15	12	25	蓝色
K- 07 10 04 62	15	12	25	黑色
K- 07 10 04 64	18	14	28	蓝色
K- 07 10 04 66	18	14	28	黑色
K- 07 10 04 68	22	18	22	蓝色
K- 07 10 04 70	22	18	22	黑色
K- 07 10 04 72	28	23	20	蓝色
K- 07 10 04 74	28	23	20	黑色

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。