

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

属性

工作温度	-60 °C to +100 °C (PA 12)
属性	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
管长度	3 m
包装单元	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
原料	Polyamid PA 12, hard (according to DIN 73378)



提示

Operating pressure with 2.5 x overpressure safety!

其它数据应客户要求提供。

描述

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

货品

名称	管外径 Ø (mm)	管内径 Ø (mm)	20 摄氏度时的最大操作压力 (bar)	颜色
K- 07 10 04 56	12	9	38	蓝色
K- 07 10 04 58	12	9	38	黑色
K- 07 10 04 60	15	12	25	蓝色
K- 07 10 04 62	15	12	25	黑色
K- 07 10 04 64	18	14	28	蓝色
K- 07 10 04 66	18	14	28	黑色
K- 07 10 04 68	22	18	22	蓝色
K- 07 10 04 70	22	18	22	黑色
K- 07 10 04 72	28	23	20	蓝色
K- 07 10 04 74	28	23	20	黑色