

K-SPIR SCHL

Spiral hose, without fittings

属性

| | |
|------|--|
| 应用 | Air, gases, oils, greases, fuels, organic and inorganic substances |
| 工作温度 | -40 °C to +100 °C |



提示

其它数据应客户要求提供。

描述

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

货品

| 名称 | 软管内径 Ø (mm) | 软管外径 Ø (mm) | 螺旋管外径 Ø (mm) | 绕组 | Max. working pressure resistance at 23°C (bar) | 最大工作长度 (m) |
|----------------|-------------|-------------|--------------|-----|--|------------|
| K- 07 10 07 51 | 3,1 | 4,7 | 38 | 144 | 22 | 10,0 |
| K- 07 10 07 52 | 4,8 | 6,3 | 75 | 140 | 16 | 22,5 |
| K- 07 10 07 53 | 6,3 | 7,9 | 75 | 135 | 13 | 22,5 |
| K- 07 10 07 49 | 7,9 | 9,5 | 115 | 90 | 12 | 22,5 |
| K- 07 10 07 50 | 9,5 | 11,8 | 140 | 70 | 11 | 22,5 |

附件

| | |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG | Rigid adapters with kink protector |