K-SPIR SCHL

Spiral hose, without fittings

属性

应用	Air, gases, oils, greases, fuels, organic and inorganic substances
工作温度	-40 °C to +100 °C



提示

其它数据应客户要求提供。

描述

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

货品

名称	软管内径 Ø (mm)	软管外径 Ø (mm)	螺旋管外径 Ø (mm)	绕组	Max. working pressure resistance at 23°C (bar)	最大工作长度 (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

附件

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。