K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

属性

壳体	Amaplast with hinged cover
集成在壳体内	Hanging eyelets, wall mounting fixing and standing feet
规格	Pre-wired
管线入口	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
保护等级	IP 44



提示

其它数据应客户要求提供。

描述

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

货品

名称	安装	颜色
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	黄色
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	silver

附件

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。