

# K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

**HANSA FLEX**

## 属性

壳体	Amaplast with hinged cover
集成在壳体内	Hanging eyelets, wall mounting fixing and standing feet
规格	Pre-wired
管线入口	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
保护等级	IP 44



## 提示

其它数据应客户要求提供。

## 描述

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

## 货品

名称	安装	颜色
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	黄色
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	silver

## 附件

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«