


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## 属性

工作压力	See table. All values referred to a medium temperature of 50 °C (static working pressure)
空气流量	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
介质温度	-20 °C to +90 °C
壳体,套管	POM (Delrin), white
阀	Stainless steel 1.4305
弹簧,涨圈,球体	stain less steel
密封材料	NBR



## 提示

其它数据应客户要求提供。

## 描述

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## 货品

名称	接口	工作压力 (bar)	长度 (mm)	NW	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36