


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

属性

工作压力	0 - 35 bar, maximum static working pressure (non-pulsating)
空气流量	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
介质温度	-20 °C to +100 °C
解锁套管	Anodised aluminium
弹簧,涨圈,球体	stain less steel
密封材料	NBR



提示

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. 其它数据应客户要求提供。

描述

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

货品

名称	接口	颜色	长度 (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	绿色	45,0	14
K- 07 35 06 81	G 1/4 male	绿色	47,0	17
K- 07 35 06 82	G 1/8 female	绿色	45,0	14
K- 07 35 06 83	G 1/4 female	绿色	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	蓝色	45,0	14
K- 07 35 06 89	G 1/4 male	蓝色	47,0	17
K- 07 35 06 90	G 1/8 female	蓝色	45,0	14
K- 07 35 06 91	G 1/4 female	蓝色	47,0	17
K- 07 35 06 92	G 1/8 male	红色	45,0	14
K- 07 35 06 93	G 1/4 male	红色	47,0	17
K- 07 35 06 94	G 1/8 female	红色	45,0	14
K- 07 35 06 95	G 1/4 female	红色	47,0	17