


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

属性

| | |
|----------|---|
| 工作压力 | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| 空气流量 | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| 介质温度 | -20 °C to +100 °C |
| 解锁套管 | Anodised aluminium |
| 弹簧,涨圈,球体 | stain less steel |
| 密封材料 | NBR |



提示

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. 其它数据应客户要求提供。

描述

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

货品

| 名称 | 接口 | 颜色 | 长度 (mm) | SW (mm) |
|----------------|--------------|-------|------------|------------|
| K- 07 35 06 80 | G 1/8 male | 绿色 | 45,0 | 14 |
| K- 07 35 06 81 | G 1/4 male | 绿色 | 47,0 | 17 |
| K- 07 35 06 82 | G 1/8 female | 绿色 | 45,0 | 14 |
| K- 07 35 06 83 | G 1/4 female | 绿色 | 47,0 | 17 |
| K- 07 35 06 84 | G 1/8 male | Brown | 45,0 | 14 |
| K- 07 35 06 85 | G 1/4 male | Brown | 47,0 | 17 |
| K- 07 35 06 86 | G 1/8 female | Brown | 45,0 | 14 |
| K- 07 35 06 87 | G 1/4 female | Brown | 47,0 | 17 |
| K- 07 35 06 88 | G 1/8 male | 蓝色 | 45,0 | 14 |
| K- 07 35 06 89 | G 1/4 male | 蓝色 | 47,0 | 17 |
| K- 07 35 06 90 | G 1/8 female | 蓝色 | 45,0 | 14 |
| K- 07 35 06 91 | G 1/4 female | 蓝色 | 47,0 | 17 |
| K- 07 35 06 92 | G 1/8 male | 红色 | 45,0 | 14 |
| K- 07 35 06 93 | G 1/4 male | 红色 | 47,0 | 17 |
| K- 07 35 06 94 | G 1/8 female | 红色 | 45,0 | 14 |
| K- 07 35 06 95 | G 1/4 female | 红色 | 47,0 | 17 |