

K-LKS 5 UWB

Stems and plugs DN 5

属性

工作压力	0 - 35 bar, maximum static working pressure (non-pulsating)
空气流量	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
介质温度	-20 °C to +100 °C
原料	黄铜



提示

其它数据应客户要求提供。

货品

名称	定义	颜色	SW (mm)
K- 07 35 01 54	Stem, I.D. 6	绿色	-
K- 07 35 01 55	Stem, I.D. 6	Brown	-
K- 07 35 01 56	Stem, I.D. 6	蓝色	-
K- 07 35 01 57	Stem, I.D. 6	红色	-
K- 07 35 01 58	Plug G 1/8 male	绿色	17
K- 07 35 01 59	Plug G 1/4 male	绿色	17
K- 07 35 01 60	Plug G 1/8 female	绿色	17
K- 07 35 01 61	Plug G 1/4 female	绿色	17
K- 07 35 01 62	Plug G 1/8 male	Brown	17
K- 07 35 01 63	Plug G 1/4 male	Brown	17
K- 07 35 01 64	Plug G 1/8 female	Brown	17
K- 07 35 01 65	Plug G 1/4 female	Brown	17
K- 07 35 01 66	Plug G 1/8 male	蓝色	17
K- 07 35 01 67	Plug G 1/4 male	蓝色	17
K- 07 35 01 68	Plug G 1/8 female	蓝色	17
K- 07 35 01 69	Plug G 1/4 female	蓝色	17
K- 07 35 01 70	Plug G 1/8 male	红色	17
K- 07 35 01 71	Plug G 1/4 male	红色	17
K- 07 35 01 72	Plug G 1/8 female	红色	17
K- 07 35 01 73	Plug G 1/4 female	红色	17