


K-LKS 5 UWB

Stems and plugs DN 5

属性

| | |
|------|---|
| 工作压力 | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| 空气流量 | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| 介质温度 | -20 °C to +100 °C |
| 原料 | 黄铜 |



提示

其它数据应客户要求提供。

货品

| 名称 | 定义 | 颜色 | SW (mm) |
|----------------|-------------------|-------|---------|
| K- 07 35 01 54 | Stem, I.D. 6 | 绿色 | - |
| K- 07 35 01 55 | Stem, I.D. 6 | Brown | - |
| K- 07 35 01 56 | Stem, I.D. 6 | 蓝色 | - |
| K- 07 35 01 57 | Stem, I.D. 6 | 红色 | - |
| K- 07 35 01 58 | Plug G 1/8 male | 绿色 | 17 |
| K- 07 35 01 59 | Plug G 1/4 male | 绿色 | 17 |
| K- 07 35 01 60 | Plug G 1/8 female | 绿色 | 17 |
| K- 07 35 01 61 | Plug G 1/4 female | 绿色 | 17 |
| K- 07 35 01 62 | Plug G 1/8 male | Brown | 17 |
| K- 07 35 01 63 | Plug G 1/4 male | Brown | 17 |
| K- 07 35 01 64 | Plug G 1/8 female | Brown | 17 |
| K- 07 35 01 65 | Plug G 1/4 female | Brown | 17 |
| K- 07 35 01 66 | Plug G 1/8 male | 蓝色 | 17 |
| K- 07 35 01 67 | Plug G 1/4 male | 蓝色 | 17 |
| K- 07 35 01 68 | Plug G 1/8 female | 蓝色 | 17 |
| K- 07 35 01 69 | Plug G 1/4 female | 蓝色 | 17 |
| K- 07 35 01 70 | Plug G 1/8 male | 红色 | 17 |
| K- 07 35 01 71 | Plug G 1/4 male | 红色 | 17 |
| K- 07 35 01 72 | Plug G 1/8 female | 红色 | 17 |
| K- 07 35 01 73 | Plug G 1/4 female | 红色 | 17 |