

K-INLINE-EJEKTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

属性

属性 Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
low noise

应用 by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces

壳体 Aluminium eloxed (type VR)

喷嘴系统 Brass (type VR)

接口 插式接口



提示

其它数据应客户要求提供。

描述

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

货品

名称	喷嘴尺寸	排气接口	压缩空气接口	真空接头	抽真空度	抽吸空气消耗 (L/min)	最大抽吸能力 (L/min)	长度 (mm)	工作压力 (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0