
K-INLINE-EJEKTTOREN SLP


Inline ejectors »SLP«, plug connection

HANSA FLEX

属性

属性	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
应用	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
壳体	plastic (Typ SLP)
喷嘴系统	Brass (type VR)
接口	thread connector





提示

其它数据应客户要求提供。

描述

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

货品

名称	喷嘴尺寸	排气接口	压缩空气接口	真空接头	抽真空度	抽吸空气消耗 (L/min)	最大抽吸能力 (L/min)	长度 (mm)	工作压力 (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。