

# K-FEDERSTOESSEL

## Spring plungers

### 属性

应用	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
温度 min.	0 °C
温度 max.	80 °C
抽吸机接口	M 3 female
规格	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
弹簧路径	5,0 mm



### 提示

其它数据应客户要求提供。

### 描述

Suitable for all round or oval suction pads in our standard range.

### 货品

名称	真空接头	长度 (mm)	垂直负荷 (N/m <sup>2</sup> )
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400