K-FEDERSTOESSEL
Spring plungers

属性

应用	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
温度 min.	0 °C
温度 max.	80 °C
抽吸机接口	M 3 female
规格	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
弹簧路径	5,0 mm



提示

其它数据应客户要求提供。

描述

Suitable for all round or oval suction pads in our standard range.

货品

名称	真空接头	长度 (mm)	垂直负荷 (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。