K-WV 3/2 5/2 NAMUR

3/2 and 5/2-way spool valves



| 属性 | | | | | | |
|---------|--------------------------------------------------|--|--|--|--|--|
| 适用介质 | Air, neutral gases (filtered) | | | | | |
| 压力差 | 2 - 10 bar | | | | | |
| 许可的静态压力 | Max. 10 bar | | | | | |
| 工作温度 | -25 °C to +60 °C | | | | | |
| 电接口 | Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580 | | | | | |
| 売体 | Aluminium, anodised black | | | | | |
| 密封材料 | NBR and PUR | | | | | |



提示

其它数据应客户要求提供。

描述

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

| 货品 | | | | | | |
|----------------|--------------|--------|----------|----|---------------|--|
| 名称 | 电压 | Port 1 | 接口 3 + 5 | DN | 流量 (L/min) | |
| K- 07 15 00 01 | 230 V, 50 Hz | G 1/4 | G 1/8 | 6 | 700 | |
| K- 07 15 00 02 | 24 V DC | G 1/4 | G 1/8 | 6 | 700 | |