

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## 属性

|        |                                    |
|--------|------------------------------------|
| 介质温度   | -5 °C to +80 °C                    |
| 最大关闭压力 | 16 bar                             |
| 开关性能   | 5,5 kW                             |
| 接触方式   | NC (3-pole)                        |
| 最大开关频率 | 120 (electrical), 600 (mechanical) |
| 保护等级   | IP 54                              |



## 提示

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
其它数据应客户要求提供。

## 描述

Three-phase version

## 订购指南

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## 附加信息

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## 货品

| 名称             | 压缩空气接口 | 调节范围           |
|----------------|--------|----------------|
| K- 07 30 24 24 | G 1/2  | 2,0 - 11,0 bar |
| K- 07 30 24 26 | G 1/2  | 2,5 - 16,0 bar |