

K-DRS STANDARD

Standard pressure switches

HANSA FLEX

属性

| | |
|------|---|
| 结构类型 | Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions) |
| 应用范围 | Air, hydraulic oil, oil emulsions, water |
| 环境温度 | -25 °C to +85 °C |
| 电接口 | Tab connectors 2 x 6.3 x 0.8 |
| 开关频率 | 200/min. |
| 开关电压 | 42 V |
| 原料 | Galvanised steel |



提示

其它数据应客户要求提供。

描述

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

货品

| 名称 | 螺纹 | 调节范围 | 功能 |
|----------------|-------|-----------------|--------|
| K- 07 30 24 94 | G 1/8 | 0,3 - 2,0 bar | closer |
| K- 07 30 24 95 | G 1/8 | 1,0 - 10,0 bar | closer |
| K- 07 30 24 96 | G 1/8 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 97 | G 1/4 | 0,3 - 2,0 bar | closer |
| K- 07 30 24 98 | G 1/4 | 1,0 - 10,0 bar | closer |
| K- 07 30 24 99 | G 1/4 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 10 | G 1/8 | 0,3 - 2,0 bar | opener |
| K- 07 30 24 11 | G 1/8 | 1,0 - 10,0 bar | opener |
| K- 07 30 24 12 | G 1/8 | 10,0 - 70,0 bar | opener |
| K- 07 30 24 13 | G 1/4 | 0,3 - 2,0 bar | opener |
| K- 07 30 24 14 | G 1/4 | 1,0 - 10,0 bar | opener |
| K- 07 30 24 15 | G 1/4 | 10,0 - 70,0 bar | opener |