

# K-DRS STANDARD

Standard pressure switches

**HANSA FLEX**

## 属性

|      |   |
|------|---|
| 结构类型 | Spring-loaded diaphragm (NBR); Spring-loaded piston;<br>(10 to 70 bar versions) |
| 应用范围 | Air, hydraulic oil, oil emulsions, water  |
| 环境温度 | -25 °C to +85 °C  |
| 电接口  | Tab connectors 2 x 6.3 x 0.8  |
| 开关频率 | 200/min.  |
| 开关电压 | 42 V  |
| 原料   | Galvanised steel  |



## 提示

其它数据应客户要求提供。

## 描述

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## 货品

| 名称             | 螺纹    | 调节范围            | 功能     |
|----------------|-------|-----------------|--------|
| K- 07 30 24 94 | G 1/8 | 0,3 - 2,0 bar   | closer |
| K- 07 30 24 95 | G 1/8 | 1,0 - 10,0 bar  | closer |
| K- 07 30 24 96 | G 1/8 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 97 | G 1/4 | 0,3 - 2,0 bar   | closer |
| K- 07 30 24 98 | G 1/4 | 1,0 - 10,0 bar  | closer |
| K- 07 30 24 99 | G 1/4 | 10,0 - 70,0 bar | closer |
| K- 07 30 24 10 | G 1/8 | 0,3 - 2,0 bar   | opener |
| K- 07 30 24 11 | G 1/8 | 1,0 - 10,0 bar  | opener |
| K- 07 30 24 12 | G 1/8 | 10,0 - 70,0 bar | opener |
| K- 07 30 24 13 | G 1/4 | 0,3 - 2,0 bar   | opener |
| K- 07 30 24 14 | G 1/4 | 1,0 - 10,0 bar  | opener |
| K- 07 30 24 15 | G 1/4 | 10,0 - 70,0 bar | opener |