

K-DRS W BAJONETT

Pressure switches - changeover type

属性

| | |
|------|---|
| 结构类型 | Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions) |
| 环境温度 | -25 °C to +85 °C |
| 电接口 | Bayonet coupling connector Ø 2.5 mm |
| 开关频率 | 200/min. |
| 测量电压 | 42 V |
| 功能 | Changeover |
| 原料 | Galvanised steel |



提示

其它数据应客户要求提供。

描述

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

货品

| 名称 | 螺纹 | 调节范围 |
|----------------|-------|-----------------|
| K- 07 30 28 36 | G 1/8 | 0,5 - 2,0 bar |
| K- 07 30 28 37 | G 1/8 | 1,0 - 10,0 bar |
| K- 07 30 28 38 | G 1/8 | 10,0 - 70,0 bar |
| K- 07 30 28 39 | G 1/4 | 0,5 - 2,0 bar |
| K- 07 30 28 40 | G 1/4 | 1,0 - 10,0 bar |
| K- 07 30 28 41 | G 1/4 | 10,0 - 70,0 bar |

附件

K-WECHSELKONTAKT BANJOETT Changeover type bayonet coupling