


# K-BKR LEICHT IG IG

Ball valves, lightweight type, female/female thread

**HANSA FLEX**

## 属性

|      |  |
|------|--|
| 应用范围 | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| 工作压力 | Max. 40 bar  |
| 工作温度 | -15 °C to +90 °C   |
| 螺纹描述 | G thread acc. DIN EN ISO 228-1   |
| 壳体   | Nickel-plated brass  |
| 柄    | Alu, painted black   |
| 球体   | Nickel-plated brass  |
| 球密封  | PTFE   |
| 主轴密封 | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE)<br>additional PTFE-gasket  |



## 提示

其它数据应客户要求提供。

## 货品

| 名称             | DN | 螺纹      | A<br>(mm) | B<br>(mm) | L<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 33 | 8  | G 1/4   | 85,0      | 42,0      | 39,0      |
| K- 07 30 00 34 | 10 | G 3/8   | 85,0      | 42,0      | 43,0      |
| K- 07 30 00 35 | 15 | G 1/2   | 85,0      | 46,0      | 50,0      |
| K- 07 30 00 36 | 20 | G 3/4   | 105,0     | 53,0      | 58,0      |
| K- 07 30 00 37 | 25 | G 1     | 105,0     | 57,0      | 69,0      |
| K- 07 30 00 38 | 32 | G 1 1/4 | 130,0     | 70,0      | 81,0      |
| K- 07 30 00 39 | 40 | G 1 1/2 | 130,0     | 76,0      | 93,0      |
| K- 07 30 00 40 | 50 | G 2     | 165,0     | 92,0      | 110,0     |